

Topog-E® Series 3000 gaskets

They're what your boiler would choose...

MATERIAL COMPOSITION AND APPLICATION

Topog-E® S-3000 gaskets are especially designed for inspection ports of boilers and tanks. They provide reliable sealability with low stress and exceptional dimension stability.

This form of gasketing is processed by layering over 150 thin films of expanded pure polytetrafluoroethylene (PTFE). The result is a bi-directional, soft, highly compressible gasket for longer life and trouble-free sealing. Its form-in-place versatility is perfect for sealing boiler plates that are worn, warped or scored. The high compressibility of the **Topog-E® S-3000** gasket enables it to effectively fill flange imperfections for a tight, leak-free seal. Unlike conventional PTFE which is prone to cold flow **Topog-E® S-3000** has good creep resistance and bolt torque retention properties. It does not support bacterial growth or cause product contamination and is FDA compliant. It has virtually no shelf-life concerns since PTFE is unaffected by normal environmental conditions.

Topog-E® S-3000 has excellent resistance properties to chemical attack. It is ideal for most chemical services at temperatures to -450°F (-268°C) to 600°F (315°C) and pressure to 3,000 psi (206 bar). When high levels of CO₂ in the steam and condensate require increased levels of neutralizing amines to prevent condensate corrosion. This chemical injection with increasing alkalinity could potentially contest the upper limits of resistance with other gasket compounds. In challenging thermal cycling and elevated temperature applications, the **Topog-E® S-3000** gasket solution can reduce the process safety and production downtime risks caused by the use of an incorrect gasket material.

Topog-E® Series 3000 gasket advantages:

High adaptability, suitable for flanges with corrosion and with uneven sealing surface

Pressure test and service with the same gasket

Very easy installation and removal

Anti-sticking material, low effort for surface cleaning when installing a new gasket

No embrittlement of the gasket in storage or in service

Pure PTFE, conforms to FDA standards

SIZES

Topog-E® Series 3000 gaskets are available in almost any shape or size. As a standard, **Topog-E® S-3000** is provided in 1/8" (3.2mm) thickness. Other thicknesses are available upon request.

ORDERING

Please either contact your local distributor for **Topog-E® Series 3000** gaskets or contact Topog-E® directly for details of your nearest distributor.

SERVICE SUMMARY

Temperature: -450°F (-268°C) to +600°F (+315°C) **Pressure:** 3,000 psig (206 bar)

M Factor: 2 (Smooth Flange Surface)

Y Stress: 2,800 psi (Smooth Flange Surface)



The Topog-E® Gasket Co. · 1224 North Utica · Tulsa, Oklahoma 74110
T: 918-587-6649 · F: 918-587-6961 · E: info@topog-e.com · W: www.topog-e.com

All information in this data sheet is based on data believed to be reliable, however we make no guarantee or warranty of performance of Topog-E® Series 3000 gaskets. Because there are many application-specific factors that can affect service life it is always advisable to first test Topog-E® Series 3000 gaskets in a particular application to determine their ultimate suitability.