

Series FGR/FGT/FGDW Textiles

Material Composition and Application

Series FGR braided rope is fabricated with high quality texturized fiberglass yarns that will not burn and will withstand continuous exposure to temperatures of 1000°F (520°C). This material resists most acids and alkalis and is unaffected by most bleaches and solvents. It is highly flexible and conformable.

Series FGT and FGDW Woven Fiberglass Tape and Dropwarp Tape are specialized materials designed for high-temperature gasketing applications in environments with temperatures up to 1000°F (538°C). These tapes are engineered to withstand extreme heat, pressure, and chemical exposure, ensuring reliable performance in demanding industrial settings. Both are available with PSA backing for ease of installation.

Temperature Resistance: 1000°F (520°C)

Size and Shape:

Round ¼" – 1-½"

Flat Tape 1" – 8"

Drop Warp 1" – 3"

TadPole – Custom

Material Composition:

Texturized Fiberglass Yarns

FGR SPOOL SIZE
¼" x 575 FT
⅜" x 500 FT
½" x 275 FT
⅝" x 200 FT
¾" x 75 FT
1" x 75 FT
1-¼" x 30 FT
1-½" x 25 FT

FGT/FGDW ROLL SIZE			
WIDTH	⅛" THK	⅜" THK	¼" THK
1"	100 FT	100 FT	50 FT
1-½"	100 FT	100 FT	50 FT
2"	100 FT	100 FT	50 FT
3"	100 FT	100 FT	50 FT
4"	100 FT	100 FT	50 FT
6"	100 FT	100 FT	50 FT
8"	100 FT	100 FT	50 FT



O.G. Supply, LLC

1150 Guadalupe Drive, Cibolo, TX 78108
 (210) 370.7990 Toll Free: (800) 394.7846
 info@ogsupply.com www.ogsupply.com

